

Turnkey VDS41022

Solutions Brief

The Future of Storage Expansion

Viking Enterprise Solutions' VDS41022 JBOD enclosure is a high- density SAS-4 data storage solution that packages 102, 3.5-inch HDDs running at 12 Gb/s SAS with two active 24 Gb/s I/O modules. Providing leading-edge density, capacity and \$/TB, the VDS41022 offers a reduced footprint for the largest of today's most demanding data centers.

- ◆ Enabler for Petabytes storage expansion
- ◆ SAS-4 24Gb/s, high bandwidth, high IOPS with low latency for performance demanding applications
- ◆ Turnkey expansion storage solutions with options for half and fully populated, 16TB, 18TB, 20TB and higher capacity HDD's
- ◆ The ultra, high density, 4U, 102-bay expansion storage solution, can be housed in a standard data center rack/cabinet (<1 meter)
- ◆ SAS-4 host connectivity expansion storage solution with 102 drives in 4U form factor
- ◆ 5-Year support and warranty included

Target Applications



Genomic



Analytical



Enterprise IT




Video Surveillance



AI & ML



Media & Entertainment



The VDS41022 expansion enclosure was designed to enable vertical scaling of storage capacity in order to match the needs of a wide range of enterprise-grade storage applications requiring full redundancy. The VDS41022 enables the expansion of external storage in file, block and object storage format through a standard SAS-4 24Gb/s interface between the JBOD and any standard storage server. The VDS41022 provides leading-edge density, capacity, aggressively priced, and offers a reduced footprint for even the largest of today's most demanding data centers.

VDS41022 Highlights

- ◆ High availability - dual, 24Gb/s SAS-4 I/O modules for failover, fully operational even with a single I/O module
- ◆ Multiple drive partitioning/split-bus zoning modes, hot-pluggable I/O controllers, drives, regulators and fan modules
- ◆ Redundant and high efficiency advanced SFF-8674, 24 Gb/s SAS-4 expansion ports
- ◆ Modular design increases product configuration flexibility
- ◆ SAS point-to-point connectivity isolates drive failures, increasing reliability & fault tolerance, while improving performance
- ◆ SAS daisy-chain expansion to additional storage arrays & other SFF-8674 SAS compliant host/expansion ports
- ◆ Single SAS-4 I/O module configuration is available, featuring four 4-wide, 24 Gb/s mini SAS HD ports with support for 12 Gb/s-6 Gb/s SAS and 6 Gb/s SATA drives
- ◆ High density expansion enclosure fits in standard 1 meter data center rack and/or cabinet including CMA (cable management arm)
- ◆ Turnkey expansion storage solutions with options for 16TB and higher capacity HDD fully integrated
- ◆ Includes 5-year support/warranty

Expansion Storage Workloads

- ◆ Backup and Archive Plus DR
- ◆ Software Defined Storage Environments
- ◆ Big Data
- ◆ Data Farm
- ◆ Data Analytics for ML and AI
- ◆ Private Cloud Infrastructures

Expansion Storage Offerings

P/N	Description
VDS41022-CH-10	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 816TB SAS RAW capacity
VDS41022-CH-11	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 918TB SAS RAW capacity
VDS41022-CH-12	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 1020TB SAS RAW capacity
VDS41022-CH-05	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 1632TB SAS RAW capacity
VDS41022-CH-06	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 1836TB SAS RAW capacity
VDS41022-CH-07	VES VDS41022 High Density JBOD - 4U-102/bay with Dual 24Gb/s SAS IOM and 2040TB SAS RAW capacity

SOLUTIONS BRIEF

AC Power

- ◆ Input voltage 200-240V AC
- ◆ Input frequency: 50-60 Hz
- ◆ Power supplies: 2 (n+1)
- ◆ Input current: 9.4 amps max @ 200V AC per power supply
- ◆ Maximum system continuous DC output power rating: 1600W

Hot-swappable Components

- ◆ Two JBOD IO modules
- ◆ Two AC to DC power modules
 - Two 1600W power supplies
 - Two +5V regulators per enclosure/system provide hard drive power
- ◆ Two independent AC power inputs
- ◆ Up to 102 drives in the main bay

Firmware

- ◆ SCSI enclosure services (SES) 3.0-based firmware

Drive Partitioning/ Split Bus Zoning

- ◆ Drive array can be zoned in four pre-defined zoning configurations supported by the I/O modules

Capacity

- ◆ 102-drive capacity per 4U enclosure
 - 102 drive slots compatible with LFF or SFF drives
 - 12Gb/s supported on all drive slots

Failure Notifications

- ◆ SCSI enclosure services (SES-3.0) over in-band interface and via system status and FRU LEDs

Host Expansion Interfaces

- ◆ Two SAS-4 JBOD I/O modules, each with 4-wide, SFF-8674, 24 Gb/s mini SAS HD expansion ports

Operating Environment

- ◆ Temperature: 5° to 35°C
- ◆ Relative humidity: 20% to 80% (non-condensing)
- ◆ Altitude: -200 ft to 10,000 ft
- ◆ Shock: 3.5G at 11ms, half sine wave pulse
- ◆ Vibration: 0.10G at 5 Hz to 500 Hz
- ◆ Acoustics (declared sound power): 92 dB with I/O modules; at idle/active operation tested to ISO 7779

Non-operating Environment

- ◆ Temperature: 5°C to 45°C
- ◆ Relative humidity: 10% to 90% (non-condensing)
- ◆ Altitude: -200 ft to 10,000 ft
- ◆ Shock: 7G at 11ms, 1/2 sine wave pulse
- ◆ Vibration: 3G at 5 Hz to 500 Hz

Disk Drives

- ◆ Form factor: 3.5-inch HDDs
- ◆ Interface: 12Gb/6Gb SAS; 6Gb SATA
- ◆ Power: 10W per drive

Safety Standards

- ◆ UL 60950
- ◆ CSA 22.2-950

Quality Standards

- ◆ Manufactured under an ISO 9002 quality system

Environment Protection

- ◆ RoHS & WEEE compliant

4U Rackmount Enclosure

- ◆ Dimensions: 6.9 in. H X 17.2 in. W X 39.4 in. D (17.2 cm H X 43.8 cm W X 100.0 cm D)
- ◆ Weight with drives: 275.0 lbs. (124.7 kg) max
- ◆ Standard rackmount rail kit with optional cable management system

Electromagnetic Emissions & Immunity Standards

- ◆ CE Mark
- ◆ EN55022: 2010
- ◆ EN61000 3-2:2014
- ◆ EN61000 3-2:2013
- ◆ FCC Class A
- ◆ Canadian IECs-003

Monitoring & Reporting

- ◆ Monitors temperature, power, cooling (including fan speed control), disk drives, and I/O modules
- ◆ In-band reporting of all FRU and chassis serial numbers, part numbers and revisions

ABOUT VIKING ENTERPRISE SOLUTIONS

Viking Enterprise Solutions, a product division of Sanmina Corporation (NASDAQ: SANM), provides advanced data center products including solid-state memory and disk-based storage server appliances, JBOD storage systems and other products for a variety of data center and storage applications. Viking Enterprise Solutions award-winning products are tailored for integration into OEM, system integrator and data center products, reducing development and operating costs while improving time-to-market. More information is available at www.vikingenterprisesolutions.com.



Phone
Email
Website

855-639-7838
channel@vikingenterprisesolutions.com
www.vikingenterprisesolutions.com



Copyright © 2023 Viking Enterprise Solutions, all rights reserved.